


Order No.: 5XA51283NS008P | GTIN (EAN): 4058352271865

Product description: DL20,PL1.2s,5340lm840,Plus



4058352271865
5XA51283NS008P

LED 4000K / CRI ≥ 80 $\Phi_{\text{H}} 5340 \text{ lm}$



DL® 20 LED, mast luminaire, primary light control with reflector, highly specular, primary optical cover: cover, of toughened safety glass of clear glass with excellent transmission level, light distribution: PL1.2s, light emission: direct distribution, primary light characteristic: symmetric, installation type: post-top, LED High Power LED, rated luminous flux: 5.340 lm, light colour: 840, colour temperature: 4000K, control gear: ECG Plus, control: overheat protection, power reduction, digital communication interface, constant luminous flux control, time-dependent luminous flux control, flexible luminous flux parameterisation, electronic power reduction, mains connection: 220..240V, 50/60Hz, start of lifetime: 53 W, end of lifetime: 54 W, reduction: 24 W, luminaire housing, upper part, of cast aluminium, powder-coated, Siteco® metallic grey (DB 702S), diameter: 690 mm, height: 690mm, spigot size: 76mm (post-top), luminaire housing, of cast aluminium, powder-coated, Siteco® metallic grey (DB 702S), protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, impact resistance: IK08, permissible ambient temperature for indoor applications: -30..+35°C, standard-compliant lighting for roads and squares, packaging unit: 1 piece



Lamps: LED
Wt. (kg): 13.5
GTIN (EAN): 4058352271865

5XA51283NS008P

The luminaire contains built-in LED lamps

A++

A+

A

B

C

D

E

LED

The LED-lamps cannot be changed in the luminaire

874/2012

